

Standing Digital Signage >



FEATURES



Key Feature of **Standing Digital Signage**

- » High-Resolution Visuals
- » User-Friendly Interface
- » Customizable Content
- » 10Points Capacitive Touch Screen


1 Content Management

1 Remote Management

1 Integration



SPECIFICATIONS:

Standing Digital Signage (Capacitive touch)						
Image						
Specification	Type	Parameter				
	Model	NEX-DK32	NEX-DK43	NEX-DK50	NEX-DK55	NEX-DK65
Display parameters	LCD size	32	43	50	55	65
	Response time	6 ms				
	Frequency	60Hz				
	Display colors	1.07B (10bit)				
	Viewing angle	178°(H/V)				
	Life span	≥30000 hrs				
	Contrast ratio (Typ)	≥1100:1				
	Brightness (Typ)	400~450cd/m ²				
	Pixel pitch	0.372×0.372mm				
	Resolution	1920*1080	3840*2160			
	Back light source	ELED				
	Max visual area (mm)	698.4×392.85	940.9×529.3	1095.84×616.41	1209.6×680.4	1428.48×803.52
Speakers	Soundtrack	2				
	Power	8Ω 2×5W				
Touch & Writing	Touch mode	capacitive touch				
	Supported system	Windows10/Windows8/Windows7/Windows XP/Android				

	Touch points	10 point touch
	Input mode	Finger, Capacitive pen
Motherboard solution port		
System	Chip solution	MEDIATEK MT9679
	System version	Android 14.0
	Clock rate	1.4GHz
	CPU	Cortex-A73
	GPU	Mali-G52
	RAM	4GB
	ROM	64GB

SPECIFICATIONS:

	OSD	English (Australia)/English (India)/English (United Kingdom) /English (United States) /Español (España) /Español (Estados Unidos) /Filipino /Français (Canada) /Français (France) /Hrvatski /Indonesia /IsiZulu /Italiano /Kiswahili /Lat Viešu /Lietuvių /Magyar /Melayu /Nederlands /Norsk bokmål /Polski /Português (Brasil) /Português (Portugal) /Română /Rumantsch /Rumantsch /Sloven čina /Slovenščina /Suomi /Svenska /Tiếng Việt /Türkçe /Ελληνικά /Русский /Српски /Українська /فارسی /தமிழ் /हिन्दी /ไทย /日本語 /Afrikaans /Català /Čeština /Dansk /Deutsch /中文 (简体) /中文 (繁體)
Bluetooth	Version	5.4
	Operation frequency	2.4GHz
	Operation distance	0~10m
	Remark	Built-in Bluetooth
Wi-Fi	Version	802.11ac/b/g/n/a
	Operation frequency	2.4GHz/5GHz
	Operation distance	0~10m
	Remark	Built-in Wi-Fi mode
	WIFI level	WIFI6
Onboard interface	HDMI IN	1
	USB2.0	1
	USB 3.0	1
	RJ45 IN	1
	Type-c	1

	Earphone	1				
	12V DC IN	1				
Power parameters						
	Voltage	Rated 100-240V~, 50/60H				
	Max power consumption	53W	70W	85W	95W	125W
	Standby power consumption	≤1W				
Size & weight						
	Bare dimension	1550*440*26mm	1730*576*26mm	1800*663*26mm	1850*728*26mm	1950*850*26mm
	Packing dimension	1640*560*160mm	1825*700*160mm	1880*800*160mm	1925*855*160mm	2050*970*170mm
	Net weight	23KG	32KG	40KG	44KG	56.5KG
	Gross weight	26KG	36KG	44.5KG	49KG	62.5KG
Accessories						
	Power cord	×1				
	Hex wrench	×1				
	Base	×1				
	Certificate/Warranty card	×1				
Environmental factors						
	Working temperature	0°C~40°C				
	Working humidity	10%~90%RH				
	Storage temperature	-20°C~60°C				
	Storage humidity	10%~90%RH				
	Working elevation	<5000m				