

Standing Digital Signage >



Key Feature of **Standing Digital Signage**

- » High-Resolution Visuals
- » User-Friendly Interface
- » Customizable Content
- » 10Points Capacitive Touch Screen


1 Content Management

1 Remote Management

1 Integration



SPECIFICATIONS:

Standing Digital Signage (Capacitive touch)		
Image		
Specification	Type	Parameter
	Model	NEX-DK75
Display parameters	LCD size	75
	Response time	6 ms
	Frequency	60Hz
	Display colors	1.07B (10bit)
	Viewing angle	178°(H/V)
	Life span	≥30000 hrs
	Contrast ratio (Typ)	≥1100:1
	Brightness (Typ)	400~450cd/m2
	Pixel pitch	0.372×0.372mm
	Resolution	3840*2160
	Back light source	ELED
	Max visual area (mm)	1611 × 906
Speakers	Soundtrack	2
	Power	8Ω 2×5W
Touch & Writing	Touch mode	capacitive touch
	Supported system	Windows10/Windows8/Windows7/Windows XP/Android

	Touch points	10 point touch
	Input mode	Finger, Capacitive pen
Motherboard solution port		
System	Chip solution	MEDIATEK MT9679
	System version	Android 14.0
	Clock rate	1.4GHz
	CPU	Cortex-A73
	GPU	Mali-G52
	RAM	4GB
	ROM	64GB
	OSD	English (Australia)/English (India)/English (United Kingdom) /English (United States) /Español (España) /Español (Estados Unidos) /Filipino /Français (Canada) /Français (France) /Hrvatski /Indonesia /IsiZulu /Italiano /Kiswahili /Lat Viešu /Lietuviy /Magyar /Melayu /Nederlands /Norsk bokmål /Polski /Português (Brasil) /Português (Portugal) /Română /Rumantsch /Rumantsch /Sloven čina /Slovenščin /Suomi /Svensk a/Tiếng Việt /Türkçe /Ελληνικά /Русский /Српски /Українська /فارسی /தமிழ் /ភាសាខ្មែរ /हिन्दी /日本語 /Afrikaans /Català /Čeština /Dansk /Deutsch /中文 (简体) /中文 (繁體)
Bluetooth	Version	5.4
	Operation frequency	2.4GHz
	Operation distance	0~10m
	Remark	Built-in Bluetooth
Wi-Fi	Version	802.11ac/b/g/n/a
	Operation frequency	2.4GHz/5GHz
	Operation distance	0~10m
	Remark	Built-in Wi-Fi mode
	WIFI level	WiFi-6
Onboard interface	HDMI IN	1
	USB2.0	1
	USB 3.0	1
	RJ45 IN	1
	Type-c	1

	Earphone	1
	12V DC IN	1
Power parameters	Voltage	Rated 100-240V~, 50/60H
	Max power consumption	125 w
	Standby power consumption	≤1W
Accessories	Power cord	×1
	Hex wrench	×1
	Base	×1
	Certificate/Warranty card	×1
Environmental factors	Working temperature	0°C~40°C
	Working humidity	10%~90%RH
	Storage temperature	-20°C~60°C
	Storage humidity	10%~90%RH
	Working elevation	<5000m