

15U Wall Mount Network Rack

– 600x600

Part No.: **NX-WM-15U-6060-E**

Short Description:

The **NX-WM-15U-6060-E** is a compact 15U wall-mount network rack designed for secure and space-efficient installation of networking and IT equipment. Its reliable welded frame structure supports over 60 kg of load, while adjustable 19-inch mounting rails, a reversible tempered glass front door, and removable locking side panels provide flexible installation, easy equipment access, and enhanced security. The cabinet also features convenient cable management and integrated cooling for efficient equipment operation.



Key Features:

- Overall thickness 1.0 mm, rail thickness 1.0 mm;
- Front glass door with small lock;
- Removable side with small lock;
- 2*Low-noise cooling fans
- 2*Red decorative door strips;
- Blank panel on top and bottom;
- 15sets cage nuts;

Additional Information:

Feature	Description
15U Wall-Mount Design	Space-efficient 19-inch rack solution with a 600mm depth for networking and IT equipment.
Welded Frame Structure	Robust welded construction provides reliable structural stability and supports over 60 kg of loading capacity.
Adjustable Mounting Rails	Adjustable front and rear vertical rails accommodate different equipment installation requirements.
Tempered Glass Front Door	Locking and reversible transparent tempered glass door provides equipment visibility, security, and flexible access.
Removable Side Panels	Locking, removable side panels simplify equipment installation, maintenance, and accessory integration.
Cable Management	Top cable brush panel provides convenient cable entry while helping minimize dust ingress.
Integrated Cooling	Two low-noise cooling fans are installed on the top panel to support effective airflow and equipment cooling.
Fixed Shelf Support	Fixed shelf design provides additional equipment support and is suitable for wall-mount and 2-post open-rack applications.
Cold-Rolled Steel Construction	Shelf manufactured from SPCC cold-rolled steel for reliable strength and durability.
Power Distribution Unit	Includes a PDU with British standard outlets and plug, 3-meter cable, aluminum alloy construction, and 16A/220V input.